


Pelican's range of converting equipment is designed and developed to achieve high standards in flexible packaging. Its state-of-the-art technology offers excellence in converting solutions.

Machine Speed	:	400 m/min	Laminates Substrates:
			BOPP
Maximum Web-Width	:	1130 mm & 1330 mm	PP CAST
Maximum Laminating Width	:	1115 mm & 1315 mm	LDPE / HDPE
Minimum Film Width	:	600 mm	VARIOUS COEX
			NYLON CAST
Maximum Reel diameter Unwinder & Rewinder	:	1000 mm	PET
Maximum Reel Weight Unwinder & Rewinder	:	800 kgs	OPA
			PAPER
Core Diameter for Unwinder	:	3" (76mm) & 6" (152mm)	
Core Diameter for Rewinder	:	6" (152 mm)	

WEB CONFIGURATION



DELICAN

ROTOFLEX PVT. LTD.

Road No. 8, Plot No. 2319-2321,
GIDC Metoda, Dist. Rajkot
(Gujarat) INDIA.

Tel.: +91(2827)287422, 287433
Fax: +91(2827)287499




Planetary Gear Box



Panel AC



Bi-2 Mixer



Dancer & Chill Roll



3 - Roller Nip System



Solvent - Less
Laminator



Sololam^{PLUS}


Innovative
engineering at..EXCELLENCE...

e-mail: sales@pelican.in
website: www.pelican.in

The machine

Created to cover the growing needs of solvent-less lamination on flexible packaging market. Enhanced performance, on one hand, and the easy operating features on the other, are the main reasons to select this machine, joined with its ability to handle a wide range of laminating jobs. The machine has been specially designed, focusing on short and medium runs on solvent-less applications over plastic films.

By perfectly integration of the new generation of electronics and ergonomically designed mechanical components, the machine is made to deliver optimum performance and productivity.



Control system

Servo based closed loop controller for web handling by using latest generation of electronics. Entire machine operation is controlled and supervises by high performance motion controller having its own intelligent software.

Master operator control panel consists of touch screen operating interface facilitates ease in operation. Safety of operator, machine and electronic modules are achieved with the help of necessary hardware protection and intelligent software routines.



Frame Structure

Distinctively designed and precisely machined, strong and sturdy, steel frame structure, with stiffening tie-rods; maintains accuracy over long dependable life and ensures less vibration even with optimum line speed. The structure enhances illumination of the working area.

The mechanical construction of each component, which undergoes extensive tests, ensures optimum performance and longer equipment life.

Shaft-less Unwinders & Rewind Group

Shaft-less unwind & rewind web tension controlled by using latest generation servo motor and servo drive. The system maintains the set tension precisely throughout the reel run. The system mainly composed of AC servo drive and servo motor, pneumatically loaded low friction dancing roller assembly and load cell for tension feed-back and actual tension display.

The unwind & rewind arms move on high precision linear bushings and supported on ground chrome-plated steel bars.

The metering cylinder design advantages :

The cylinder includes an innovative floating system which, by means of a touch-screen, allows the operator to set and modify the adhesive quantity easily. The system facilitates cleaning operation easier.

Adhesive Metering System.

Adhesive applicator zone comprises multi roller transfer system, (1) R1 roller and (2) R2 roller are metering Roller. (3) R3 Transfer Rubber Roller (4) R4 is Applicator Roller and (5) R5 is rubber covered Pressure Roller, through the high precision machining and high quality engineering resulted more uniform and accurate coating across the width of the web.



R1 & R2 Rollers: Specially designed, jacketed type, high precision grounded chrome-plated steel rollers, heating through water/oil to a maximum temperature of 80 C. A micro-metric device used to control the gap between the R1 & R2 rollers. This gap allows initial adjustment of adhesive's amount need to transfer. The gap can be adjusted considering viscosity or type of adhesive used on the machine.

R3 Roll (the Metering Roll) is clad with vulcanized rubber and is rectified at the width of the support to be laminated. R3 Roll handles the metering and transfers adhesive from R2 to R4, the applicator roll.

The R1 Roll, not driven at time of production but can be rotate manually if required.

The R2 & R3 rolls, driven by common AC servo motor & gear box and controlled through a servo drive. The speed of the R2 & R3 is proportionate to machine speed and can be vary to control the amount of adhesive to apply.

R4 Roll transfers adhesive from the roller R3, to the substrate to laminate. It is made of chrome-plated steel, jacketed type ensures uniform heating across the roller face length.

R5 Roll made of steel and covered with hard rubber, presses the R4 roll by means of two pneumatic cylinders, so that it guarantees the total transfer of adhesive to the web.

Laminating Unit

The laminator unit comprises a heated chrome-plated, ground steel roll, a rider roll, coated with hard rubber & chrome plated steel back-up roller which is driven by pneumatic pistons which can be adjusted at both ends. The Steel back-up roller is press against the rubber roller for a total parallelism and to avoid any rubber roller flexion.

The laminator steel roll is driven by an independent motor synchronized with the applicator unit motor by load cells, so the tension on the web carrying the adhesive to the point of lamination can be controlled with great precision.

Idle Rollers

Specially designed, dynamically balanced low friction-low inertia idle rollers made of Aluminum alloy, mounted on low friction bearings, enhance rotational smoothness.

Solvent - Less Laminator

LOWenergy
CONSUMPTION

UNIQUE SERVICE SUPPORT

SAFETY ON
BOARD

FAST
JOB CHANGE OVER



Sololam PLUS